



**GOLLMER & HUMMEL**  
hoses for heroes

# GH PROGRESS FLAME HP

**SPECIAL HOSE PROGRESS FLAME HP WITH FLAME-RESISTANT RUBBER COMPOUND,  
DEVELOPED FOR FIGHTING FOREST AND WILDLAND FIRES**

## MATERIAL CONSTRUCTION

### Jacket lining:

- Warp: High-tenacity polyester
- Weft: Polyamide; circular woven
- The special jacket construction ensures outstanding adhesion and much lower pressure loss compared to a 100% polyester jacket lining
- Totally embedded in the rubber, offering optimum protection against mechanical damage

### Rubberized lining and jacket:

- Specially developed flame-resistant rubber compound, extruded through the weave in a special one-step production process
- More flexible and supple than comparable products

## ADVANTAGES

- ✓ Flame-resistant rubber compound
- ✓ Specially developed for forest and wildland firefighting
- ✓ Very lightweight and highly flexible (also at extremely low temperatures)
- ✓ Small coil diameter
- ✓ Excellent resistance to aging and ozone
- ✓ Resistant to mildew and rot
- ✓ Easy to repair

## AT A GLANCE

### Standard colors

red

---

## CONTACT

Gollmer & Hummel GmbH  
Gässlesweg 23  
75334 Straubenhardt

**T** +49 (0) 7082 9434-0

**F** +49 (0) 7082 9434-99

**E** [info@gollmer-hummel.de](mailto:info@gollmer-hummel.de)

---

PRESSURES

Test pressure:  
Maintained for 1 min:  
In accordance with DIN 14811:  
Ø 25 - 75: 24 bar

In accordance with BS 6391:2009:  
Ø 38 - 89: 22.5 bar

Order hose sample >>

DATASHEET

Inside diameter in mm	Weight in g/m	Wall thickness in mm	Working pressure in bar	Max. working pressure in bar	Burst pressure in bar
25	240	2.6	40	48	120

**i** Specifications apply only to the hose. The potential working pressure may be lower than specified above for hose lines with couplings due to the nominal pressure of the couplings or the type of assembly.

PRODUCT IMAGES

